

PRODUCT DATA SHEET – 310XX0000

As of: 15.07.2020

| | | |
|-----------------------------|---|--|
| Article number: | 310090000 – 10 x 6 mm 310080000 – 15 x 6 mm |  |
| Product name: | Ceramic Sealing tape | |
| Description: | Resistant self-adhesive fibreglass tape for sealing duct joints. Suitable for use in fire-rated and smoke extraction ductwork | |
| Material: | Fibreglass | |
| Fiber diameter: | Ø 3,2 µm | |
| Adhesive: | Acryl-Dispersion | |
| Colour: | White | |
| Lidding material: | PE-Silicone film | |
| Adhesive bonder | Nonwoven-fleece | |
| Classification temperature: | + 1200 °C | |
| Melting point: | > 1330 °C | |
| Density: | 180 – 240 kg/m ³ | |
| Tensile strength: | > 350 kPa | |
| Properties: | <ul style="list-style-type: none"> ● one-sided self-adhesive ● solvent-free ● asbestos-free | |

The intention of this product leaflet is to provide non-binding information and should only be interpreted as such. The information takes the current state of technical developments and developments in the chemical industry. We reserve the right to make modifications relating to the product as well as to develop it further. No liability on our part can be derived from this. Users should check the suitability of the product for the intended purpose by conducting their own tests.

| | |
|----------------|---|
| Delivery unit: | 10 x 6 mm: Roles à 10 m, box à 300 m, pallet à 12.000 m 15 x 6 mm: Roles à 10 m, box à 200 m, pallet à 8.000 m |
| Remarks: | Due to the excellent biosolubility, the intilized fibreglass is classified as non-carcinogenic |